



Runa



Distributed by Tile Space, stocked products are featured on our website, all other products are available on indent.

Nexion interprets Stone

RUNA COLLECTION

Runa collection brings the essence of the noble and sophisticate character of the slates found in the countryside, villages and historical cities of Northern Europe. Stones that blend harmoniously with the elements of nature in a very contemporary style.

Though these stones are common in Europe, finding the nicest one is not easy.

Nexion has worked to recreate the taste of those suggestive slates that blend naturally in the architectural works of contemporary urban contexts. By the perfection of design and the hands of skilled craftsmen, Nexion has given to the surface of Runa the character of the best natural stones, strong at sight and gentle at touch.

The result is a ceramic collection that returns the sober and harmonious elegance of slates with a modern and dynamic mood. A collection that brings the best of the inspiring Italian contemporary design to any type of ambience and location.

Nexion about

Nexion is a joint venture company created by Ceramiche Speranza, a best-in-class Italian firm founded in 1961, and Simpolo, since 1977 one of the leading Indian producers of ceramics and sanitary ware.

With mastery of technology and design, we turn the best of the Italian tradition and lifestyle into contemporary ceramic surfaces that can be source of inspiration for architects and designers around the world.

Open-minded and keen to learn from customers and partners, we are committed to deliver the best quality and service and we believe that our work ends when our clients fulfill their resires and achieve their goals.





120x240 cm | 80x160 cm | 60x120 cm | 60x60 cm | 30x60 cm



120x240 cm F14RNAGONRO Grigio Chiaro



80x160 cm **F86RNAGONRO** Grigio Chiaro




60x120 cm F62RNAGONRO Grigio Chiaro




60x60 cm F60RNAGONRO Grigio Chiaro





Surface pattern options



33,3%









120x240 cm F14RNAG1NRO Grigio Scuro



80x160 cm **F86RNAG1NR0** Grigio Scuro



60x120 cm F62RNAG1NRO Grigio Scuro



60x60 cm F60RNAG1NR0 Grigio Scuro



30x60 cm F63RNAG1NRO Grigio Scuro

Full-body coloured porcelain stoneware | Rectified | 9 mm thickness



120x240 cm F14RNABONRO Beige



80x160 cm **F86RNABONRO** Beige



60x120 cm F62RNABONRO Beige



60x60 cm F60RNABONRO Beige



30x60 cm F63RNABONRO Beige



Nexion recommends 2 mm joint for optimal aesthetics taking advantage of the tiles caliber in multi-sized applications.

Both cement and epoxy grout can be used; grout-design color matching advisable for optimal aesthetics. It is not recommended to use grouting with coloured pigments in contrast with the colour of the tiles.



120x240 cm F14RNAKONRO Nero



80x160 cm F86RNAKONRO Nero



60x120 cm F62RNAKONRO Nero



60x60 cm F60RNAKONRO Nero



30x60 cm F63RNAKONRO Nero

Nexion quality standards ALL TESTS ARE CARRIED OUT BY ITALIAN LABORATORIES ACCREDITED ACCORDING TO ISO/IEC 17025:2005

Standards according to ISO 13006: Annex G - EN 14411: Annex G. Dry - Pressed Ceramic Tiles.

QUALITY	TECHNICAL FEATURE	STANDARD	REQUIREMENTS			NEXION Values			
ITEMS	TECHNICAL FEATURE	METHOD ISO			Side < 1200 mm Side ≥ 1200		200 mm		
DIMENSIONS AND SURFACE QUALITY	LENGH AND WIDTH	UNI EN ISO 10545-2	%	mm	%	mm	%	mm	
	LENGH AND WIDTH		±0,6%	±2,0	±0,2%	±2,0	±0,1%	±1,5	
	THICKNESS		±5%	±0,5	±5%	±0,5	±4%	±0,36	
	STRAIGHTNESS OF SIDES		±0,5%	±1,5	±0,2%	±1,5	±0,1%	±1,5	
	RECTANGULARITY		±0,5%	±2,0	±0,33%	±1,5	±0,1%	±1,5	
	FLATNESS		±0,5%	±2,0	±0,26%	±1,5	±0,2%	±1,5	
	SURFACE QUALITY		tiles shall be fro	A minimum of 95% of the tiles shall be free from visible defects that would impair the appearance of a major area of tiles.		Compliant			
	WATER ABSORPTION	UNI EN ISO 10545-3	E _b ≤0,5% Individual maximum : 0,6% (absorbed water mass)		E _b ≤0,2% (absorbed water mass)				
	BREAKING STRENGTH		Min 10	≥ 2000 N					
PHISICAL PROPERTIES	MODULUS OF RUPTURE	UNI EN ISO 10545-4	R ≥ 35 N/mm² minimum 32 Not applicable to tiles with breaking strength ≥ 3000 N		R ≥ 45 N/mm² minimum 40 Not applicable to tiles with breaking strength ≥ 3000 N				
	FROST RESISTANCE	UNI EN ISO 10545-12	Required		Compliant				
	SCRATCH HARDNESS (Mohs scale)	EN 101	Min 6		Compliant				
	SURFACE ABRASION	UNI EN ISO 10545-7	0 (100 cycles) 1 (150 cycles) 2 (600 cycles) 3 (1500 cycles) 4 (6000 cycles) 5 (> 12000 cycles)		5 (Maximum level)				
	COEFFICIENT OF LINEAR THERMAL EXPANSION FROM AMBIENT TEMPERATURE TO 100° C (K ⁻¹)	ISO 10545-8	Required		6 x 10 ⁻⁶ K ⁻¹ max				
	CRAZING RESISTANCE	ISO 10545-11	Required		Compliant				
	RESISTANCE TO THERMAL SHOCK	ISO 10545-9	10 Cycles Min		Compliant				
	IMPACT RESISTANCE	ISO 10545-5	Min 0,55		Compliant				
	BULK DENSITY	DIN 51082	2,2 g/cc Min		Compliant				
CHEMICAL PROPERTIES	RESISTANCE TO STAINING	UNI EN ISO 10545-14	Minimum Class 3		5				
	RESISTANCE TO HOUSEHOLD CHEMICALS AND SWIMMING POOL SALTS	UNI EN ISO	Minimum UB		GA (No visible effect)				
	RESISTANCE TO HIGH AND LOW CONCENTRATIONS OF ACIDS AND ALKALIS	10545-13	To be re	GLA - GHA (No visible effect)					
	SLIP RESISTANCE	DIN 51130			R10				
	OLII TILOIOTANOL	DIN 51097		B (A+B)					

Packaging info

Shipments to domestic markets (India)

Nominal	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)	Box x pallet	Sq. Mts x pallet	Pallet weight
120x240	9	1	2,87	60,33	16	45,92	965,28
80x160	9	1	1,28	26,78	35	44,63	937,30
60x120	9	2	1,43	30,00	34	48,72	1020,00
60x60	9	3	1,07	22,53	40	42,92	901,20
30x60	9	6	1,07	22,45	40	42,80	898,00

Worldwide shipments

Nominal	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)	Box x pallet	Sq. Mts x pallet	Pallet weight
120x240	9	1	2,87	60,33	15	43,05	904,95
80x160	9	1	1,28	26,78	35	44,63	937,30
60x120	9	2	1,43	30,00	34	48,72	1020,00
60x60	9	3	1,07	22,53	40	42,92	901,20
30x60	9	6	1,07	22,45	40	42,80	898,00

Size

5120						
Nominal Size cm	Actual Size cm					
120x240	119,8x239,8					
80x160	79,8x159,8					
60x120	59,8x119,8					
60x60	59,8x59,8					
30x60	29,8x59,8					





Nexion International Pvt. Ltd. 1102, Shapath V, S.G. Road, Ahmedabad 380 015 Gujarat, India Email: info@nexion.in www.nexion.in